



“Gheorghe Asachi” Technical University of Iasi, Romania



OPTIMIZING MESH CONFIGURATIONS IN SOLAR CHIMNEY SYSTEMS: A CFD-BASED APPROACH FOR ENHANCED ENERGY EFFICIENCY AND PERFORMANCE

**Jihen Mahdhi¹, Ons Ghriss², Humberto Garcia Castellanos³,
Abdallah Bouabidi⁴, Ali Keçebaş⁵, Yashar Aryanfar^{6*}**

¹Research Unit of Mechanical Modeling, Energy and Materials(M2EM), National School of Engineers of Gabes (ENIG), University of Gabes, UR17ES47, ZrigGabes 6029, Gabes-Tunisia

²National Engineering School of Gabes (ENIG), Research Laboratory “Processes, Energetics Environment and Electrical Systems”, Gabes University, Omar Ibn Kattab ZRIG, Gabes, 6029, Tunisia

³Engineering Sciences, Tecnológico Nacional de México IT Ciudad Juárez, Juarez, Chihuahua, Mexico

⁴Unit of Mechanical Modeling, Energy & Materials (M2EM), UR17ES47, National School of Engineers of Gabes (ENIG)/ High Institute of Industrial Systems of Gabès (ISSIG), Gabes University, Avenue of Omar Ib-Elkhattab, 6023, Zrig, Gabes, Tunisia

⁵Department of Energy Systems Engineering, Technology Faculty, Muğla Sıtkı Koçman University, 48000 Menteşe, Muğla, Turkey

⁶Department of Electric Engineering and Computation. Autonomous University of Ciudad Juárez. Av. Del Charro 450 Norte. Col. Partido Romero. Juárez, Chihuahua, México

Abstract

The present study investigates the effect of mesh configurations on the performance of a solar chimney (tower) system using Computational Fluid Dynamics (CFD) simulations. This research focuses on optimizing mesh density to enhance the accuracy of temperature, velocity, and pressure predictions in the solar tower, which significantly impact energy efficiency. Unlike previous studies, which primarily focused on geometrical design and system layout, this article introduces a novel meshing strategy that balances computational efficiency and simulation accuracy. Four different mesh types were analyzed, with the finest meshes (M3 and M4) showing the closest alignment to experimental data, achieving an error margin below 4%. The results revealed that finer meshes provided more accurate representations of temperature profiles, pressure gradients, and velocity distributions, particularly near the chimney's axis, optimizing the overall system's performance. The minimum total pressure values for meshes were 5.61 Pa, 6.25 Pa, 6.61 Pa, and 6.86 Pa, respectively, indicating how mesh density influences internal pressure dynamics. This study highlights the importance of mesh selection in CFD simulations and recommends future designs to incorporate adaptive mesh refinement techniques for better simulation efficiency. The findings offer valuable insights into the design and optimization of solar tower systems, promoting enhanced power generation and efficiency, which are essential for scaling renewable energy projects. Future research could explore broader applications of this methodology to optimize other renewable energy systems.

Key words: CFD, mesh effect, numerical analysis, solar energy, solar tower

Received: August, 2023; Revised final: October, 2024; Accepted: November, 2024

* Author to whom all correspondence should be addressed: e-mail: yashar.aryanfar@gmail.com, al216622@alumnos.uacj.mx; Phone: +525626776998