



"Gheorghe Asachi" Technical University of Iasi, Romania



FINITE ELEMENT ANALYSIS OF STRESS DISTRIBUTION AND DISPLACEMENT IN THE HUMAN KNEE JOINT: ENHANCING OSTEOARTHRISIS DIAGNOSIS

Denisa Șmadici^{1,2}, Ana Tufescu^{1*}, Viorel Paleu^{1*}

¹*Mechanical Engineering, Mechatronics and Robotics Department (I.M.M.R), "Gheorghe Asachi" Technical University of Iași, 43 Prof. Dimitrie Mangeron Blvd, Iași, 700050, Romania*

²*Faculty of Medical Bioengineering, "Grigore T. Popa" University of Medicine and Pharmacy of Iași, Str. M.Kogalniceanu, no. 9-13, Iași, Postal Code 700454, Romania*

Abstract

The knee joints of humans undergo continuous degradation with aging, often resulting in the onset of osteoarthritis (OA) accompanied by significant functional impairments. The non-invasive early diagnosis of this disorder through vibroarthrography (VAG) necessitates the acquisition and signal processing of vibroacoustic signals obtained from the knee joint during repeated flexion and extension movements of the leg. Establishing the optimal diagnostic procedure for the knee joint requires determining the requisite movements to derive significant diagnostic parameters from VAG signals, with a particular focus on the maximum contact pressure in the knee joint for various positions between the tibia and femoral bones. This paper presents a finite element analysis (FEM) of a human knee joint, emphasizing the critical movements that must be incorporated into the optimal non-invasive diagnostic procedure for OA, with a specific emphasis on the assessment of maximum contact pressure.

Key words: bioengineering, diagnosis, FEM analysis, knee joint, osteoarthritis

Received: November, 2024; Revised final: May, 2025; Accepted: June, 2025

* Author to whom all correspondence should be addressed: e-mail: ana.tufescu@academic.tuiasi.ro, viorel.paleu@academic.tuiasi.ro