



“Gheorghe Asachi” Technical University of Iasi, Romania



INTEGRATED PROCESS BASED ON BIOLOGICAL METHOD AND ELECTROCOAGULATION FOR SLAUGHTERHOUSE WASTEWATER: NEW APPROACHES FOR TREATMENT WITH FRESHWATER SNAILS (*VIVIPARUS CONTECTUS*, *PLANORBIS RUBRUM*, *MELANOIDES TUBERCULATA*)

Ayşenur Ögedey¹, Filiz Kutluyer Kocabaş^{2*}, Volkan Kizak², Mehmet Kocabaş³,
Fulya Benzer⁴, Mine Erişir⁵, Hayrullah Ögedey²

¹Munzur University, Faculty of Engineering, Department of Civil Engineering, 62000, Tunceli, Turkey

²Munzur University, Fisheries Faculty, 62000, Tunceli, Türkiye

³Karadeniz Technical University Faculty of Forestry, Department of Wildlife Ecology and Management 61080, Trabzon, Türkiye

⁴Department of Food Engineering, Munzur University, Faculty of Engineering, Tunceli, Turkey

⁵Department of Basic Sciences, Fırat University, Faculty of Veterinary, Elazığ, Türkiye

Abstract

As a potential pollution source, slaughterhouse wastewater (SWW) with development of the meat production and processing sector is a threat in the world. Therefore, the determination of economical, favourable, cost-effective and proper treatment method is crucial for sustainable environmental protection. This study focused on the performance and efficiency of a two-stage process combining biological treatment (BT) with freshwater snails and electrocoagulation (EC) of SWW. *Viviparus conetectus*, *Planorbis rubrum*, *Melanoides tuberculata* were used in primary treatment while secondary treatment was realized with EC process. The EC of SWW was performed for reducing both turbidity and chemical oxygen demand (COD) concentration to levels compliant with direct-discharge regulations. In addition, the stirring speed, current density, initial pH and reaction time were assessed for evaluation the optimum EC condition. Oxidative stress biomarkers and some antioxidants were assessed in freshwater snails exposed to SWW after 24 and 96 h. The best removal efficiencies of COD (91.43%) and turbidity (92.42%) were obtained at pH 5 and 20 min of operational time by *P. rubrum*. Notably, MDA (Malondialdehyde) was highest level in *M. tuberculata* compared to *V. conetectus* and *P. rubrum*. Overall, removing organic and inorganic pollutants from SWW could be provided with the hybrid process BT/EC as a combining approach.

Key words: biological treatment, electrocoagulation, freshwater snail, slaughterhouse wastewater

Received: November, 2024; Revised final: February, 2025; Accepted: March, 2025

* Author to whom all correspondence should be addressed: e-mail: filizkutluyer@hotmail.com; Phone: +90 0 554 407 80 65