Environmental Engineering and Management Journal

July 2019, Vol. 19, No. 7, 1079-1095 http://www.eemj.icpm.tuiasi.ro/; http://www.eemj.eu



"Gheorghe Asachi" Technical University of lasi, Romania



FAST REMOVAL OF MALACHITE GREEN FROM AQUEOUS SOLUTIONS USING HIGHLY HYDROPHOBIC WATER–DISPERSIBLE MAGNETIC NANOCOMPOSITE

Mohsen Nekoeinia^{1*}, Akram Khodadeh-Tehrani¹, Omran Moradlou², Abolfazl Semnani³, Majid Kolahdoozan⁴, Hojjat Kazemi⁵, Maryam Kabiri Dehkordi¹

¹Department of Chemistry, Payame Noor University, P.O. Box 19395-4697, Tehran, Iran ²Department of Chemistry, Faculty of Physics and Chemistry, Alzahra University, P.O. Box: 1993893973, Tehran, Iran ³Department of Chemistry, Faculty of Sciences, Shahrekord University, Shahrekord, Iran ⁴Department of Chemistry, Shahreza Branch, Islamic Azad University, Shahreza, Iran ⁵Department of Instrumental Analysis, Research Institute of Petroleum, 14665137 Tehran, Iran

Abstract

Release of dyes without performing adequate treatment into the water can lead to environmental risk and serious health problems. The development of effective and economic adsorbent materials for the removal of dyes from industrial wastewaters has gained great consideration in recent years. In the present study, a novel bio-based nanocomposite has been developed for ultrasound-assisted adsorption of malachite green (MG) from aqueous solutions. The synthesized adsorbent consisting of both hydrophobic surface and hydrophilic polar functional groups was prepared by covalent binding of epoxidized sunflower oil (ESFO) on the surface of silica-coated magnetite nanoparticles. The synthesized sorbent was characterized by FE-SEM, EDS, FT-IR, XRD, VSM and thermal analysis. The effects of experimental parameters including pH, amount of sorbent, temperature and uptake time were investigated for MG adsorption on Fe₃O₄@SiO₂-ESFO sorbent using Box-Behnken design. At the optimized conditions, the adsorption capacity of the magnetic nanocomposite for MG was found to be 4.97 mg g⁻¹ according to the removal yield of 90.0%, while 88% of the adsorption occurred at the first 1 min, and the adsorption equilibrium was achieved in few minutes. The results showed that the proposed Fe₃O₄@SiO₂-ESFO sorbent exhibits a strong adsorption affinity to MG, and the adsorption isotherms are well described by Freundlich model. A thermodynamic study of the adsorption indicated that MG adsorption on sorbent was an endothermic and spontaneous phenomena.

Keywords: epoxidation, magnetic nanosorbent, Malachite green, sunflower oil, wastewater treatment

Received: August, 2019; Revised final: December, 2019; Accepted: February, 2020; Published in final edited form: July, 2020

^{*}Author to whom all correspondence should be addressed: e-mail: m_nekoeinia@pnu.ac.ir; Phone: +98-038-32223328